



Absolute Maximum Ratings (Ta=25°C)

	UNIT	SPEC.
IF	mA	30
IFp	mA	100
V _R	V	5
IR	uA	100
Top	°C	-25~+80
Tstg	°C	-30~+85

Part No.	Chip				Lens Appearance	Electro-optical Data (At 20mA)				Viewing Angle 2θ 1/2 (deg)±5
	Material	Emitted Color	λ _p (nm)	Δλ (nm)		V _f (V)		I _v (mcd)		
						Typ.	Max.	Min.	Typ.	
BL-HH036A	GaP/GaP	Bright Red	700	90	Water Clear	2.2	2.6	0.3	1.0	120
BL-HG036A	GaP/GaP	Green	568	30		2.2	2.6	4.0	12.0	
BL-HGC36A	GaP/GaP	Green	568	30		2.1	2.6	4.5	14.0	
BL-HX136A	GaP/GaP	Hi-Eff Green	568	30		2.0	2.6	5.0	15.0	
BL-HW136A	GaP/GaP	Pure Green	555	25		2.2	2.6	0.8	2.5	
BL-HY036A	GaAsP/GaP	Yellow	585	35		2.1	2.6	1.6	5.0	
BL-HE036A	GaAsP/GaP	Hi-Eff Red	630	45		2.0	2.6	2.5	7.0	
BL-HE136A	GaAsP/GaP	Hi-Eff Red	640	45		2.0	2.6	2.5	7.0	
BL-HA136A	GaAsP/GaP	Soft-Orange	610	35		2.0	2.6	1.5	4.5	
* BL-HS036A	GaAlAs/GaAs	Super Red	660	20		1.7	2.6	4.0	12.0	
* BL-HS136A	GaAlAs/GaAs	Super Red	660	20		1.8	2.6	4.5	14.0	
* BL-HD036A	GaAlAs/GaAs	Super Red	660	20		1.8	2.6	6.0	20.0	
* BL-HF036A	GaAlAs/GaAlAs	Super Red	660	20		2.1	2.6	10.0	38.0	
* BL-HF136A	GaAlAs/GaAlAs	Super Red	660	20		2.1	2.6	13.5	40.0	
* BL-HF536A	GaAlAs/GaAlAs	Super Red	660	20		2.2	2.6	9.0	28.0	